



STATE OF FLUID	MAXIMUM PREMISSIBLE WORKING PRESSURE
OIL OR PULSATING FLOW 80°C OR BELLOW	1.0MPa
STEADY FLOW 80°C OR BELOW	1.4MPa

12×25キリ M22ボルト穴
(JIS10K-250A管フランジ)

003	BYPASS		1Set	
2-3	O-RING	NBR	1	
2-2	NUT	SS400	1	UNI-CR PLATING
2-1	SPLIT PIN	SUS304	1	
209	SPRING GUIDE	CAC406C	1	
208	SPRING	SUS304WPB	1	
207	RUBBER SEAT	NBR	1	
206	FOLLOWE	C3604BD	1	
205	DISC GUIDE	CAC406	1	
204	PLATE	FC200	1	
203	BODY SEATRING	CAC406	1	
202	DISC	FC200	1	
201	BODY	FC200	1	
No.	Name of Parts	Materials	Q'ty	Descriptions

TEST PRESSURE

BODY (Water)	2.1 MPa
SEAT (Water)	1.54 MPa

名 称	<WATER HMMER ABSORPTION TYPE> CAST IRON 10K FLANGED HAMMERLESS CHEC VALVE 250A		製品記号 F10HC
	承認	検図	製図

承認	検図	製図	年月日	尺度
<i>S. Nishikawa</i>	<i>S. Takano</i>	T.Nishikawa	2021.04.14	