



SIZE		d	L	FLANGE					do	H
inch	mm			D	C	n	h	t		
1½B	40A	38	115	140	105	4	19	18	25	105
2B	50A	50	130	155	120	4	19	18	25	115

STATE OF FLUID	MAXIMUM PREMISSIBLE WORKING PRESSURE
OIL OR PULSATING FLOW 80°C OR BELOW	1.0MPa
STEADY FLOW 80°C OR BELOW	1.4MPa

2-2	TRAS SCREWS	SUS304	1	
2-1	O-RING	NBR	1	
212	HANDWHEEL	POM	1	
211	DISC	PTFE	1	
210	STEM	C3604BD	1	
209	SPRING	SUS304WPB	1	
208	BONNET	C3604BD	1	
207	GASKET	NON-ASBESTOS	1	
206	SEATRING	C3604BD	1	
205	DISC GUIDE	CAC406	1	
204	RUBBER SEAT	NBR	1	
203	BODY SEATRING	CAC406	1	
202	DISC	C3604BD	1	
201	BODY	FC200	1	
No.	Name of Parts	Materials	Q'ty	Descriptions

TEST PRESSURE

BODY (Water)	2.1 MPa
SEAT (Water)	1.54 MPa

<WATER HAMMER ABSORPTION TYPE> CAST IRON 10K FLANGED HAMMERLESS CHECK VALVES		FIGURE F10HC
--	--	-----------------

Approval	Check	Drawing	Date	Scale
<i>T. Nishikawa</i>	<i>T. Nishikawa</i>	T. Nishikawa	2021.04.15	

<b>Yamato Valve Co., Ltd.</b>	図番	Drawing No. FBCDF-R005N
-------------------------------	----	----------------------------