



PRESSURE-TEMPERATURE SPECIFIC

STATE OF FLUID	MAXIMUM PREMISIBLE WORKING PRESSURE
OIL OR PULSATING FLOW 60°C OR BELOW	1.0 MPa
STEADY FLOW 60°C OR BELOW	1.4 MPa

<LINING SPECIFIC>

- PAINT : NYLON 12
- SCOPE : INSIDE & OUTSIDE OF PARTS
- COLOR : GRAY
- THICKNESS : 300 μm OR ABOVE

003	BYPASS		1set	
2-3	O-RING	NBR	1	
2-2	NUT	SUS304	1	
2-1	SPLIT PIN	SUS304	1	
209	LABEL	POLYESTER	1	
208	SPRING	SUS304WPB	1	
207	RUBBER SEAT	NBR	1	
206	FOLLOWER	C3604BD	1	
205	DISC GUIDE	CAC406	1	
204	PLATE	CAC406	1	
203	BODY SEATRING	CAC406	1	
202	DISC	CAC406	1	
201	BODY	FC200	1	
No.	Name of Parts	Materials	Q'ty	Descriptions

TEST PRESSURE

BODY (Water)	2.1 MPa
SEAT (Water)	1.54 MPa

<WATER HAMMER ABSORPTION TYPE>
 NYLON-LINING LEAD-CUT CAST IRON
 10K FLANGED HAMMERLESS CHECK VALVES 250A

FIGURE
 NF10HCN

Approval	Check	Drawing	Date	Scale
<i>S. Nishikawa</i>	<i>S. Terao</i>	T.Nishikawa	2021.04.20	

Yamato Valve Co., Ltd. 図番 Drawing No. FBCDJ-P029C